



RVL-1 FIBER OPTIC LINK SYSTEM

GNSS solution for remote antenna installations



The RVL-1 FIBER is an affordable Multi-Constellation fiber optic solution for remote GPS antenna installations. RVL-1 covers frequency ranges from 800 MHz up to 1800 MHz and passes all of the GNSS frequencies (GPS, GLONASS, GALILEO, BEIDOU, SBAS, L-BAND) over fiber from a few meters up to 1,524 meters (5,000 feet).



The RVL utilises the advantages of Fiber Optic cable over coaxial including:

- Greater distance for remote antenna (up to 1,524 meters)
- Lower signal loss during transmission
- Security as the cable does not radiate signals.
- Immune to environmental factors that affect copper
- Insulated cable so no electrical current can flow through, therefore providing the ultimate in lightning and surge protection.
- Immune to electrometric interference and Radio-frequency interference.
- Fiber cable can run beside industrial equipment without concern
- The cable is lightweight, thin and durable making installation easier to handle, whilst also taking up less space.
- Lower costs to maintain than copper cable.

This unit has been designed to operate on 12V to 36V AC or DC, allowing the use of low voltage NEC electrical wiring standards to be used at installation. The RVL-1 is designed to operate with any TNC GNSS antenna with at least 34dB gain for a complete solution.

RVL-1 GPS fiber optic link is patented technology. (US8032031 B2)

Forsberg Services Ltd

Richmond House, White Cross, Lancaster, LA1 4XF, UK

Phone: +44 (0) 1524 383320

Fax: +44 (0) 1524 382939

Web: <http://www.forsbergservices.co.uk>

V1.02

Forsberg Services Ltd (Deutschland)

Hülshagen 68, 31714 Lauenhagen, Germany

Phone: +49 9367 987 8080

Fax: +49 9367 987 8084

Web: <http://www.forsbergservices.de>

PIONEERING SOLUTIONS IN NAVIGATION TECHNOLOGY

www.forsbergservices.co.uk

RVL-1

GNSS solution for remote antenna installations

RavenLink TRANSMITTER

Product Overview

Antenna Requirements:

- Connection: TNC
- Gain: 34dB +6/-3 dB
- Impedance: 50Ω
- Power: 5 VDC (minimum 8mA)
- Frequency: 800MHz to 1800 MHz
- Power Connection: 2 Pin 12-24V AC or DC
- Input Voltage: AC/DC 12-24V 50/60 Hz @ 100-600mA

Output Connection:

ST Type Fiber Optic Connector for Simplex Multimode 50/125 Micron Cable

Fiber Length:

System allows Fiber Runs of up to 1524 meters (5000 feet) of 50/125 Fiber Optic Cable

Enclosure: Die cast, Aluminium

Colour: Beige (Powder Coated)

Relative Humidity: 0-100% Condensing

Storage Temp: -50°C to +85°C

Operating Temp: -40°C to +70°C

Accessories: Power Supply (516816), Power Cable (516818)

Altitude: 6,096m (20,000 ft)

System Propagation Delay: 15ns (does not include fiber optic cable delay)

US Patent 8032031 B2

RavenLink RECEIVER

Product Overview

Input Connection: ST Type Fibre Optic Connector for Simplex Multimode 50/125 Micron Cable

Input Power: 5 to 12 VDC @ 85mA (powered from DC bias of GPS Receiver)

Output Connection: BNC 50 OHM Female

Frequency: 800MHz to 1800 MHz

Enclosure: Extruded Aluminium

Colour: Natural

Relative Humidity: 0-95% Non-Condensing

Storage Temp: -40°C to +85°C

Operating Temp: 0°C to +50°C

Accessories: Antenna Fault Reporting LED:

Green – Good;

Red – Fault

Altitude: 6,096m (20,000 ft)



Forsberg Services Ltd

Richmond House, White Cross, Lancaster, LA1 4XF, UK

Phone: +44 (0) 1524 383320

Fax: +44 (0) 1524 382939

Web: <http://www.forsbergservices.co.uk>

V1.02

Forsberg Services Ltd (Deutschland)

Hülshagen 68, 31714 Lauenhagen, Germany

Phone: +49 9367 987 8080

Fax: +49 9367 987 8084

Web: <http://www.forsbergservices.de>